

235系列单孔PCB端子排
235 Series single hole PCB terminal block

订货号 Order No.

IEC额定电流/电压/接线面积
IEC Current/Voltage/Wire range [A]/[V]/[mm²]

UL额定电流/电压/接线面积
UL Current/Voltage/Wire range [A]/[V]/[AWG]

剥线长度/焊针脚长度/焊针尺寸
Strip length/Pin length/Pin header size [mm]

通道数 Poles No.



间距 Pitch: 5.0mm
235202/010 ● 灰色 Gray
235203/010
235224/010

17.5 / 320 / 0.2-1.5

10 / 300 / 24-16

8-9 / 3.6 / 0.4X0.8

2-24



间距 Pitch: 5.0mm
235202 ● 灰色 Gray
235203
235224

17.5 / 320 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.6 / 0.4X0.8

2-24



间距 Pitch: 7.5mm
235302/010 ● 灰色 Gray
235303/010
235324/010

17.5 / 630 / 0.2-1.5

10 / 300 / 24-16

8-9 / 3.6 / 0.4X0.8

2-24



间距 Pitch: 7.5mm
235302 ● 灰色 Gray
235303
235324

17.5 / 630 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.6 / 0.4X0.8

2-24



间距 Pitch: 10.0mm
235402/010 ● 灰色 Gray
235403/010
235424/010

17.5 / 1000 / 0.2-1.5

10 / 300 / 24-16

8-9 / 3.6 / 0.4X0.8

2-24



间距 Pitch: 10.0mm
235402 ● 灰色 Gray
235403
235424

17.5 / 1000 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.6 / 0.4X0.8

2-24

239系列单孔PCB端子排
239 Series single hole PCB terminal block

订货号 Order No.

IEC额定电流/电压/接线面积
IEC Current/Voltage/Wire range [A]/[V]/[mm²]

UL额定电流/电压/接线面积
UL Current/Voltage/Wire range [A]/[V]/[AWG]

剥线长度/焊针脚长度/焊针尺寸
Strip length/Pin length/Pin header size [mm]

通道数 Poles No.



间距 Pitch: 3.5mm
239302/010 ● 灰色 Gray
239303/010
239324/010

17.5 / 160 / 0.2-1.5

6 / 300 / 24-16

5-6 / 3.4 / 0.6X0.8

2-24




间距 Pitch: 3.5mm
239302 ● 灰色 Gray
239303
239324

17.5 / 160 / 0.2-1.5

6 / 300 / 24-16

5-6 / 3.4 / 0.6X0.8

2-24




间距 Pitch: 5.0mm
239102 ● 灰色 Gray
239103
239124

24 / 320 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.4 / 0.8X1.2

2-24



间距 Pitch: 7.5mm
239202 ● 灰色 Gray
239203
239224

24 / 630 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.4 / 0.8X1.2

2-24



间距 Pitch: 5.08mm
239152 ● 橙色 Orange
239153
239174

24 / 320 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.4 / 0.8X1.2

2-24



间距 Pitch: 7.62mm
239252 ● 橙色 Orange
239253
239274

24 / 630 / 0.2-2.5

10 / 300 / 24-14

8-9 / 3.4 / 0.8X1.2

2-24

245系列PCB端子排
245 Series PCB terminal block

订货号 Order No.

IEC额定电流/电压/接线面积
IEC Current/Voltage/Wire range [A]/[V]/[mm²]

UL额定电流/电压/接线面积
UL Current/Voltage/Wire range [A]/[V]/[AWG]

剥线长度/焊针脚长度/焊针尺寸
Strip length/Pin length/Pin header size [mm]

通道数 Poles No.



间距 Pitch: 5.0mm
245202/020 ● 灰色 Gray
245203/020
245224/020

32 / 320 / 0.2-4.0

10 / 300 / 24-12

8-9 / 4 / 0.8X1.2

2-24



间距 Pitch: 5.0mm
245202 ● 灰色 Gray
245203
245224

32 / 320 / 0.2-4.0

10 / 300 / 24-12

8-9 / 4 / 0.8X1.2

2-24



间距 Pitch: 7.5mm
245302/020 ● 灰色 Gray
245303/020
245324/020

32 / 630 / 0.2-4.0

20 / 150 / 24-12

8-9 / 4 / 0.8X1.2

2-24



间距 Pitch: 7.5mm
245302 ● 灰色 Gray
245303
245324

32 / 630 / 0.2-4.0

20 / 150 / 24-12

8-9 / 4 / 0.8X1.2

2-24



间距 Pitch: 10.0mm
245402/020 ● 灰色 Gray
245403/020
245424/020

32 / 1000 / 0.2-4.0

20 / 150 / 24-12

8-9 / 4 / 0.8X1.2

2-24



间距 Pitch: 10.0mm
245402 ● 灰色 Gray
245403
245424

32 / 1000 / 0.2-4.0

20 / 150 / 24-12

8-9 / 4 / 0.8X1.2

2-24

246系列PCB端子排
246 Series PCB terminal block

订货号 Order No.

IEC额定电流/电压/接线面积
IEC Current/Voltage/Wire range [A]/[V]/[mm²]

UL额定电流/电压/接线面积
UL Current/Voltage/Wire range [A]/[V]/[AWG]

剥线长度/焊针脚长度/焊针尺寸
Strip length/Pin length/Pin header size [mm]

通道数 Poles No.



间距 Pitch: 7.5mm
246302/020 ● 灰色 Gray
246303/020
246324/020

41 / 630 / 0.2-6.0

30 / 150 / 24-10

11-12 / 4.5 / 1X1.4

2-24



间距 Pitch: 7.5mm
246302 ● 灰色 Gray
246303
246324

41 / 630 / 0.2-6.0

30 / 150 / 24-10

11-12 / 4.5 / 1X1.4

2-24



间距 Pitch: 10.0mm
246402/020 ● 灰色 Gray
246403/020
246424/020

41 / 1000 / 0.2-6.0

30 / 150 / 24-10

11-12 / 4.5 / 1X1.4

2-24



间距 Pitch: 10.0mm
246402 ● 灰色 Gray
246403
246424

41 / 1000 / 0.2-6.0

30 / 150 / 24-10

11-12 / 4.5 / 1X1.4

2-24

